



GARLWAY MACHINERY

Concrete Mixer

Concrete Mixer

GARLWAY MACHINERY

> > >

2014

60,000

300

2,000

Garlway Machinery



: J Z C 7 5 0



1

| | |
|--|------------------------------|
| | |
| | 1.8 - 2.2 m ³ / h |
| | B V I S O |
| | 1 |
| | 2 |

J d c 3 5 0

: J D C 3 5 0



J D C 3 5 0

| | |
|--|-------------|
| | |
| | J D C 3 5 0 |
| | J D C |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

J z c 4 0 0

: J Z C 4 0 0



J Z C 4 0 0

| J Z C 3 0 0 | | 4 5 # | | |
|---------------|--|-------|--|--|
| J Z C 3 5 0 | | 4 5 # | | |
| J Z C 4 0 0 | | 4 5 # | | |
| J Z C 5 0 0 | | 4 5 # | | |
| J Z C 7 5 0 | | 4 5 # | | |
| J Z C 1 0 0 0 | | 4 5 # | | |
| J Z C 1 5 0 0 | | 4 5 # | | |

J z c 1 0 0 0

: J Z C 1 0 0 0



Discover the high-performance construction sites, road project. Features 1600L feeding, 1000L precise mixing. Enhance efficiency.

| Parameter | Value / Description |
|-----------------------|--|
| Feeding Capacity | 1600L |
| Discharge Capacity | 1000L |
| Productivity | 25 - 30m ³ / h |
| Mixing Drum Speed | 13r / min |
| Maximum Particle Size | 100mm |
| Water Supply Error | 2% |
| Discharge Height | 2500mm |
| Application Fields | General construction site, Road and bridge project, Concrete component factory |
| Selling Points | Sturdy and durable structure, Good mixing quality, Easy operation, Convenient |

J s 3 0 0 0

: J S 3 0 0 0



J S 3 0 0 0

| | |
|--|-------|
| | |
| | 6 0 0 |
| | |
| | |
| | 3 |
| | / |
| | |
| | |

: J W 4 0 0 0



| | | |
|--|-------|-------|
| | | |
| | 5 . 3 | 4 |
| | 3 7 | |
| | 2 . 6 | 3 . 2 |
| | | |

: J Z C 3 0 0



Portable cement mixer for construction and DIY. High performance, easy to use, and durable design.

| Parameter | Specification |
|------------------------|---|
| Capacity | Feeding: 480L, Discharging: 300L |
| Productivity | 9-12 m ³ /h |
| Motor Power | Mixing: 4KW, Lifting: 4KW, Pump: 0.55KW |
| Stirring Drum Speed | 17 r/min |
| Maximum Aggregate Size | 60 mm |
| Overall Dimension | 2376 × 1990 × 2750 mm |
| Overall Weight | 1650 kg |

| Application Field | Description |
|----------------------------|--|
| General Construction | Concrete mixing for civil and commercial buildings, rural self-built houses, |
| Road and Bridge Project | Concrete mixing for road laying, bridge construction, road base, bridge pier |
| Concrete Component Factory | Production of small concrete components like blocks and precast panels |

| Product Selling Point | Description |
|-----------------------|--|
| Performance | Self-falling double-cone reversing discharging, homogeneous concrete in 35-4 |
| Structure | Tires and towing frame for easy transfer, adjustable height legs for stability |
| Operation | Water supply system with motor, pump, regulating valve, and time relay control |
| Quality | Designed and manufactured according to GB/T9142-2000 standard, efficient, high |

J z c 5 0 0

: J Z C 5 0 0



J Z C 5 0 0

| | |
|-----|-----------------------------|
| | J Z C 5 0 0 |
| | 5 0 0 L |
| | 8 0 0 L |
| | 1 8 ~ 2 0 / |
| | 6 0 |
| | 1 3 r / m i n |
| | 2 0 k m / h |
| | 7 . 5 |
| | 5 . 5 |
| | 0 . 5 5 |
| | 2 4 0 0 |
| x x | 3 5 0 0 x 2 2 0 0 x 3 2 0 0 |

: J Z C 3 5 0



J Z C 3 5 0

| | |
|-------------|--|
| | |
| J Z C 3 5 0 | |
| | |
| | |
| | |
| | |

Js 500

: JS500



| | |
|--|-----------|
| | |
| | |
| | |
| | PLD HZS25 |
| | |
| | |
| | |
| | |
| | |
| | |
| | 1.5 3.8 |
| | 11 |
| | ISO SGS |

J s 1 0 0 0

: J S 1 0 0 0



J S 1 0 0 0

| | |
|--|-------------|
| | |
| | J S 1 0 0 0 |
| | |
| | |
| | |

Js 2000 Volumetric Concrete Mixer

: JS 2000



| | JS 2000 |
|--|---------|
| | 2 |
| | |
| | |
| | |
| | |
| | |
| | |

Harbor Freight Js1500

: JS1500



JS1500

| | |
|--|--------|
| | |
| | JS1500 |
| | 1.5 |
| | |
| | |
| | |

: JS750



| | |
|--|-----------------|
| | |
| | 750L |
| | 1200L |
| | 30-35 / |
| | 30 + 7.5 |
| | 80 |
| | 1.6 / 2.7 / 3.8 |

H z s 5 0

: H Z S 5 0



| | |
|-----|---------------------|
| | 50 / 30-35 / |
| | J S 1 0 0 0 |
| | 2 × 18.5 |
| | 1 0 0 0 L |
| | 1 5 0 0 L |
| | 7 2 S |
| | P L D 1 6 0 0 |
| | 3.5 × 3 |
| | 1 6 0 0 L |
| | 3 |
| | 80 |
| | 0 - 6 0 0 ± 1 |
| | 0 - 3 0 0 ± 1 |
| | 2.58m |
| | 2.7 3.8 |
| | 85.0 |
| 2.7 | 10867 × 4070 × 6560 |
| 3.8 | 17012 × 4070 × 8400 |
| 2.7 | 14870 |
| 3.8 | 17570 |

| | |
|--|--|
| | |
| | |
| | |
| | |

| | |
|--|-------------|
| | |
| | 50 / |
| | J S 1 0 0 0 |
| | |
| | |

H z s 1 2 0

: H Z S 1 2 0



H Z S 1 2 0

| | |
|--|------------------------|
| | |
| | 1 2 0 / |
| | J S 2 0 0 0 |
| | 2 × 3 7 |
| | 3 2 0 0 |
| | 2 |
| | P L D 3 2 0 0 |
| | 3 2 0 0 |
| | 2 4 |
| | 2 0 |
| | 1 2 0 |
| | ± 1 % |
| | ± 2 % |
| | 2 × 2 0 0 |
| | 3 . 8 4 . 2 |
| | 1 4 5 - 2 0 9 . 5 |
| | 9 0 × 1 0 ³ |
| | |
| | |
| | |
| | |

1 2 0

P L C

H z s 9 0

: H Z S 9 0



H Z S 9 0

| | | | | |
|---|---------------|-------------------------|-------------|-----------------|
| | | | | |
| | 9 0 | / | | |
| | J S 1 5 0 0 | | 2 × 3 0 k W | 1 5 0 0 L 6 0 S |
| | P L D 2 4 0 0 | 2 4 0 0 L | 4 | |
| | | 8 0 m m | | |
| - | | (0 - 9 0 0) ± 1 % k g | | |
| - | | 0 - 5 0 ± 1 % k g | | |
| - | | 0 - 5 0 0 0 ± 2 % k g | | |
| | | 3 × 1 0 0 t | | |
| | 3 . 8 | 4 . 2 | | |
| | | 1 6 4 | | |
| | 2 4 | x 1 0 | x 1 8 | |
| | | 6 5 0 0 0 | | |
| | | | | |
| | | | | |
| | | | | |
| | | 9 0 | | |
| | J S 1 5 0 0 | | | |
| | | | | |

| | |
|--|--|
| | |
| | |
| | |
| | |

H z s 1 8 0

: H Z S 1 8 0



| | |
|--|--|
| | |
| | 180 |
| | J S 3 0 0 0 M A 0 4 5 0 0 / 3 0 0 0 S D S H O |
| | 110 2 × 55 |
| | 3 |
| | P L D 4 8 0 0 |
| | 4800L |
| | 4 6 |
| | 0 - 1500 ± 1 |
| | 0 - 50 ± 1 |
| | 4 |
| | 200 |
| | |
| | |
| | |
| | |
| | 180 |
| | J S 3 0 0 0 |
| | |

P L C

| | |
|--|--|
| | |
| | |
| | |
| | |

H z s 7 5

: H Z S 7 5



H Z S 7 5

| | | | | | | | |
|--|--|-----------------|--|-------------|--|-------------|--|
| | | | | | | | |
| | | 7 5 / | | | | | |
| | | J S 1 5 0 0 | | 3 0 × 2 k W | | 1 . 5 2 . 4 | |
| | | P L D 2 4 0 0 4 | | 2 4 0 0 L | | 8 0 m m | |
| | | ± 2 % | | ± 1 | | | |
| | | 3 . 8 | | | | | |
| | | 2 4 3 5 0 | | x 1 0 5 9 5 | | x 1 8 7 0 4 | |
| | | 1 2 0 | | | | | |
| | | 6 0 | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | 7 5 / | | | | | |
| | | J S 1 5 0 0 | | | | | |
| | | | | | | | |
| | | | | | | | |

H z s 3 5

: H Z S 3 5



| | | |
|--|----------------|---------------------|
| | 35 / 25 - 35 / | |
| | J S 7 5 0 | |
| | 30 | |
| | 1 2 0 0 L | |
| | 0 . 7 5 | |
| | 7 5 S | |
| | P L D 1 2 0 0 | |
| | 3 6 | |
| | 1 2 0 0 L | |
| | 3 | |
| | 6 0 | 8 0 |
| | 0 - 2 5 0 | 1 |
| | 0 - 2 0 0 | 1 |
| | 2 . 8 2 m | |
| | 3 . 8 | |
| | 7 4 . 9 | |
| | 4 9 5 1 | × 3 6 5 0 × 6 2 2 5 |
| | | |
| | | |

| | |
|--|-----------|
| | |
| | J S 7 5 0 |

| | |
|--|-------------|
| | 5 0 , 0 0 0 |
|--|-------------|

| | |
|--|--|
| | |
|--|--|

Bunnings Hzs 25

: HZS 25



| | |
|--|-----------------------|
| | 25 / 20 / |
| | JS 500 |
| | 50.25 |
| | 72S |
| | 0.5 |
| | 0.75 |
| | PLD800 PLD1200 |
| | 3.5 |
| | 800 1200 |
| | 50 |
| | ± 2% ± 1 |
| | 1.5 - 3.8 m |
| | 50.25 |
| | 11693 x 13060 x 17245 |
| | 17500 |
| | |
| | |
| | |
| | |

J S 5 0 0

/



Garl way Machinery

5 5

