



GARLWAY MACHINERY

, , ,

GARLWAY MACHINERY

> > >

2014

60,000

300

2,000

Garlway Machinery



: JW5000



	5
	30
	485500
	~2.6~3.2
-	30
-	30
-	
-	
-	

: G J W 3 5 0



	3 5 0 L
	2 1 r / m i n
	5 . 5
	1 2 0 0 × 1 4 0 0
	3 5 0

: JW3000



	3
	18.5
	35
	30
	2200 x 2200 x 1600
	850

Hzs35

: HZS35



	35	/	25 - 35
	JS750		
	30		
	1200L		
	0.75		
	75S		
	PLD1200		
	36		
	1200L		
	3		
	60		80
	0 - 250		1
	0 - 200		1
	2.82m		
	3.8		
	74.9		
	4951	× 3650	× 6225

	J S 7 5 0

	5 0 , 0 0 0
--	-------------

--	--

J z c 4 0 0

: J Z C 4 0 0



J Z C 4 0 0

J Z C 3 0 0		4 5 #		
J Z C 3 5 0		4 5 #		
J Z C 4 0 0		4 5 #		
J Z C 5 0 0		4 5 #		
J Z C 7 5 0		4 5 #		
J Z C 1 0 0 0		4 5 #		
J Z C 1 5 0 0		4 5 #		

: JW500



500 L

35 rpm
7.5 KW

	500 L
	35 rpm
	7.5
	1500 × 1400

Hzs120

: HZS120



HZS120

	120 /
	JS2000
	2 × 37
	3200
	2
	PLD3200
	3200
	2 4
	20
	120
	± 1%
	± 2%
	2 × 200
	3 . 8 4 . 2
	145 - 209 . 5
	90 x 10 ³

1 2 0

P L C

: JW400



400L5.5KW

19rpm

	400L
	19 /
	5.5
	1200 × 1200
	1.2
	/

: JW6000



6 37

	6		
	37		
	4105		
	485	500	
	2.8	1	

180°

Hzs90

: HZS90



HZS90

	90 /			
	JS1500	2×30kW	1500L	60S
	PLD2400	2400L	4	
	80mm			
-	(0-900)±1%kg			
-	0-50 ±1%kg			
-	0-5000±2%kg			
	3×100t			
	3.8	4.2		
	164			
	24	x 10	x 18	
	65000			
	90			
	JS1500			

: JW1500



360°

	1.5
	1.860
	15
	360

J z c 1 0 0 0

: J Z C 1 0 0 0



Discover the high-performance construction sites, road projects. Features 1600L feeding, 1000 precise mixing. Enhance efficiency.

Parameter	Value / Description
Feeding Capacity	1600L
Discharge Capacity	1000L
Productivity	25 - 30m³ / h
Mixing Drum Speed	13 r / min
Maximum Particle Size	100mm
Water Supply Error	2%
Discharge Height	2500mm
Application Fields	General construction site, Road and bridge project, Concrete component factory
Selling Points	Sturdy and durable structure, Good mixing quality, Easy operation, Convenient

: JW2000



	2000L
	45r/min
	22
	2800 × 2800 × 2000
	1200
	270

: JW750



	750L
	1200L
	30 - 35 /
	80
	2×7.5
	7.5
	1.1
	20r/min
	2650 ×1315 ×2180
	1.2

Bunnings H z s 2 5

: H Z S 2 5



	2 5	/	2 0
	J S 5 0 0		
	5 0 . 2 5		
	7 2 S		
	0 . 5		
	0 . 7 5		
	P L D 8 0 0 P L D 1 2 0 0		
	3 . 5		
	8 0 0 1 2 0 0		
	5 0		
	± 2 % ± 1		
	1 . 5 - 3 . 8 m		
	5 0 . 2 5		
	1 1 6 9 3 × 1 3 0 6 0 × 1 7 2 4 5		
	1 7 5 0 0		

	JS500
	/

: J Z C 7 5 0



1

	1 8 - 2 2 m 3 / h
	B V I S O
	1
	2

H z s 1 8 0

: H Z S 1 8 0



	1 8 0
	J S 3 0 0 0 M A O 4 5 0 0 / 3 0 0 0 S D S H O
	1 1 0 2 × 5 5
	3
	P L D 4 8 0 0
	4 8 0 0 L
	4 6
	0 - 1 5 0 0 ± 1
	0 - 5 0 ± 1
	4
	2 0 0
	1 8 0
	J S 3 0 0 0
	P L C

Hzs 75

: HZS75



HZS75

	75 /				
	JS150030×2kW1.52.4				
	PLD240042400L80mm				
	±2%±1				
	3.8				
	24350x10595x18704				
	120				
	60				
	75 /				
	JS1500				

J d c 3 5 0

: J D C 3 5 0



J D C 3 5 0

	J D C 3 5 0
	J D C

Hzs 50

: HZS50



	5 0	/	3 0 - 3 5	/	
	J S 1 0 0 0				
	2 × 1 8 . 5				
	1 0 0 0 L				
	1 5 0 0 L				
	7 2 S				
	P L D 1 6 0 0				
	3 . 5	×	3		
	1 6 0 0 L				
	3				
	8 0				
	0 - 6 0 0	± 1			
	0 - 3 0 0	± 1			
	2 . 5 8 m				
	2 . 7	3 . 8			
	8 5 . 0				
2 . 7	1 0 8 6 7	×	4 0 7 0	×	6 5 6 0
3 . 8	1 7 0 1 2	×	4 0 7 0	×	8 4 0 0
2 . 7	1 4 8 7 0				
3 . 8	1 7 5 7 0				

	50 /
	JS1000



Garlway Machinery

55

