



GARLWAY MACHINERY

, , ,

GARLWAY MACHINERY

> > >

2014

60,000

300

2,000

Garlway Machinery



: J Z C 3 5 0



J Z C 3 5 0

	J Z C 3 5 0

: JW6000



637

	6
	37
	4105
	485500
	2.81

180°

: JW1500



360°

	1.5
	1.860
	15
	360

: JW500



500 L

35 rpm
7.5 KW

	500 L
	35 rpm
	7.5
	1500 × 1400

: JW400



19
rpm

400L5.5KW

	400L
	19 /
	5.5
	1200 × 1200
	1.2
	/

Bunnings H z s 2 5

: H Z S 2 5



	2 5 / 2 0 /
	J S 5 0 0
	5 0 . 2 5
	7 2 S
	0 . 5
	0 . 7 5
	PLD800 PLD1200
	3 . 5
	8 0 0 1 2 0 0
	5 0
	± 2 % ± 1
	1 . 5 - 3 . 8 m
	5 0 . 2 5
	1 1 6 9 3 × 1 3 0 6 0 × 1 7 2 4 5
	1 7 5 0 0

	JS500
	/

J d c 3 5 0

: J D C 3 5 0



J D C 3 5 0

	J D C 3 5 0
	J D C

: JZC300



Portable cement mixer for co
DIY. High performance, easy
durable design.

Parameter	Specification
Capacity	Feeding: 480L, Discharging: 300L
Productivity	9-12 m ³ /h
Motor Power	Mixing: 4KW, Lifting: 4KW, Pump: 0.55KW
Stirring Drum Speed	17 r/min
Maximum Aggregate Size	60 mm
Overall Dimension	2376 × 1990 × 2750 mm
Overall Weight	1650 kg

Application Field	Description
General Construction	Concrete mixing for civil and commercial buildings, rural self-built houses,
Road and Bridge Project	Concrete mixing for road laying, bridge construction, road base, bridge pier
Concrete Component Factory	Production of small concrete components like blocks and precast panels

Product Selling Point	Description
Performance	Self-falling double-cone reversing discharging, homogeneous concrete in 35-4
Structure	Tires and towing frame for easy transfer, adjustable height legs for stabiliz
Operation	Water supply system with motor, pump, regulating valve, and time relay contr
Quality	Designed and manufactured according to GB/T9142-2000 standard, efficient, hi

J z c 4 0 0

: J Z C 4 0 0



J Z C 4 0 0

J Z C 3 0 0		4 5 #		
J Z C 3 5 0		4 5 #		
J Z C 4 0 0		4 5 #		
J Z C 5 0 0		4 5 #		
J Z C 7 5 0		4 5 #		
J Z C 1 0 0 0		4 5 #		
J Z C 1 5 0 0		4 5 #		

J z c 5 0 0

: J Z C 5 0 0



J Z C 5 0 0

	J Z C 5 0 0
	5 0 0 L
	8 0 0 L
	1 8 ~ 2 0 /
	6 0
	1 3 r / m i n
	2 0 k m / h
	7 . 5
	5 . 5
	0 . 5 5
	2 4 0 0
x x	3 5 0 0 x 2 2 0 0 x 3 2 0 0

: JW2000



	2000L
	45r/min
	22
	2800 × 2800 × 2000
	1200
	270

J z c 1 0 0 0

: J Z C 1 0 0 0



Discover the high-performance construction sites, road projects. Features 1600L feeding, 1000 precise mixing. Enhance efficiency.

Parameter	Value / Description
Feeding Capacity	1600L
Discharge Capacity	1000L
Productivity	25 - 30m³ / h
Mixing Drum Speed	13 r / min
Maximum Particle Size	100mm
Water Supply Error	2%
Discharge Height	2500mm
Application Fields	General construction site, Road and bridge project, Concrete component factory
Selling Points	Sturdy and durable structure, Good mixing quality, Easy operation, Convenient

: J Z C 7 5 0



1

	1 8 - 2 2 m 3 / h
	B V I S O
	1
	2

Hzs35

: HZS35



	3 5	/	2 5 - 3 5	/	
	J S 7 5 0				
	3 0				
	1 2 0 0 L				
	0 . 7 5				
	7 5 S				
	P L D 1 2 0 0				
	3 6				
	1 2 0 0 L				
	3				
	6 0		8 0		
	0 - 2 5 0		1		
	0 - 2 0 0		1		
	2 . 8 2 m				
	3 . 8				
	7 4 . 9				
	4 9 5 1	×	3 6 5 0	×	6 2 2 5

	J S 7 5 0

	5 0 , 0 0 0
--	-------------

--	--

: G J W 3 5 0



	3 5 0 L
	2 1 r / m i n
	5 . 5
	€ 1 2 0 0 × 1 4 0 0
	3 5 0

: JW750



	750L
	1200L
	30 - 35 /
	80
	2×7.5
	7.5
	1.1
	20r/min
	2650 ×1315 ×2180
	1.2

H z s 7 5

: H Z S 7 5



H Z S 7 5

	7 5 /			
	J S 1 5 0 0 3 0 × 2 k W 1 . 5 2 . 4			
	P L D 2 4 0 0 4 2 4 0 0 L 8 0 m m			
	± 2 % ± 1			
	3 . 8			
	2 4 3 5 0 x 1 0 5 9 5 x 1 8 7 0 4			
	1 2 0			
	6 0			
	7 5 /			
	J S 1 5 0 0			

Hzs90

: HZS90



HZS90

	90 /			
	JS1500	2×30kW	1500L	60S
	PLD2400	2400L	4	
	80mm			
-	(0-900)±1%kg			
-	0-50 ±1%kg			
-	0-5000±2%kg			
	3×100t			
	3.8	4.2		
	164			
	24	x 10	x 18	
	65000			
	90			
	JS1500			

: JW3000



	3
	18.5
	35
	30
	2200 x 2200 x 1600
	850

: JW5000



	5
	30
	485500
	~2.6~3.2
-	30
-	30
-	
-	
-	

H z s 1 8 0

: H Z S 1 8 0



	1 8 0
	J S 3 0 0 0 M A O 4 5 0 0 / 3 0 0 0 S D S H O
	1 1 0 2 × 5 5
	3
	P L D 4 8 0 0
	4 8 0 0 L
	4 6
	0 - 1 5 0 0 ± 1
	0 - 5 0 ± 1
	4
	2 0 0
	1 8 0
	J S 3 0 0 0
	P L C

Hzs120

: HZS120



HZS120

	120 /
	JS2000
	2 × 37
	3200
	2
	PLD3200
	3200
	2 4
	20
	120
	± 1%
	± 2%
	2 × 200
	3 . 8 4 . 2
	145 - 209 . 5
	90 × 10 ³

1 2 0

P L C

Hzs 50

: HZS50



	5 0	/	3 0 - 3 5	/	
	J S 1 0 0 0				
	2 × 1 8 . 5				
	1 0 0 0 L				
	1 5 0 0 L				
	7 2 S				
	P L D 1 6 0 0				
	3 . 5	×	3		
	1 6 0 0 L				
	3				
	8 0				
	0 - 6 0 0	± 1			
	0 - 3 0 0	± 1			
	2 . 5 8 m				
	2 . 7	3 . 8			
	8 5 . 0				
2 . 7	1 0 8 6 7	×	4 0 7 0	×	6 5 6 0
3 . 8	1 7 0 1 2	×	4 0 7 0	×	8 4 0 0
2 . 7	1 4 8 7 0				
3 . 8	1 7 5 7 0				

	50 /
	JS1000

Harbor Freight Js1500

: JS1500



JS1500

	JS1500
	1.5

J s 1 0 0 0

: JS1000



JS1000

	JS1000

: JW4000



	5 . 3	4	
	3 7		
	2 . 6	3 . 2	

Js500

: JS500



	PLD HZS25
	1 . 5 3 . 8
	1 1
	I S O S G S

J s 3 0 0 0

: J S 3 0 0 0



J S 3 0 0 0

	6 0 0

--	--

	3

/

--	--

--	--

: JS750



	750 L
	1200 L
	30 - 35 /
	30 + 7.5
	80
	1.6 / 2.7 / 3.8

J s 2 0 0 0 V o l u m e t r i c C o n c r e t e M i x e r

: J S 2 0 0 0



	J S 2 0 0 0
	2



Garlway Machinery

55

